

```
#!/bin/ksh
#
# goActive script
#
# Configure this script when using the high availability feature of
# Network Dispatcher.
#
# This script is executed when Network Dispatcher goes into the
# 'Active' state and begins routing packets.
#
# This script must be placed in Network Dispatcher's bin directory
# (by default this is /opt/nd/dispatcher) and it needs to
# have root execute permission.
#
# le0=Ethernet, hme0=fast Ethernet
# The netmask must be the netmask of your LAN. It may be hexadecimal or octal notation.
#
echo "Removing loopback alias(es)"
ifconfig lo0:1 0 down
ifconfig lo0:2 0 down
ifconfig lo0:3 0 down
ifconfig lo0:4 0 down
ifconfig lo0:5 0 down
ifconfig lo0:6 0 down

echo "Adding NIC alias(es)"
ifconfig hme0:1 4.20.17.160 netmask 255.255.255.192 up
ifconfig hme2:1 198.77.163.160 netmask 255.255.255.192 up

ifconfig hme0:2 4.20.17.161 netmask 255.255.255.192 up
ifconfig hme2:2 198.77.163.161 netmask 255.255.255.192 up

ifconfig hme2:3 198.77.163.162 netmask 255.255.255.192 up

ifconfig hme0:3 4.20.17.163 netmask 255.255.255.192 up
```